

SGT-320PL6

Standby Power (kVA)	320
Standby Power (kW)	256
Prime Power (kVA)	290
Prime Power (kW)	232
Power Factor (cos phi)	0,8

Standby Current (A)	487
Prime Current (A)	441
Nominal Voltage (V)	380/220
Engine Speed (r.p.m)	1800
Phase	3

Engine Specifications

Engine Brand	PERKINS
Engine Model	1506A-E88TAG3
Standby Power (Kw/hp)	297 /398,28
Engine Speed (r.p.m)	1800
Total Displacement (L)	8,8
Cylinder Arrangement	6-L
Bore x Stroke (mm x mm)	112 x 149
Compretion Ratio	16,1:1
Governor Type	Electronic
Aspiration System	Turbocharged AAC
Injection	Direct
Cooling System	Water Cooled
Electrical System (VDC)	24
Oil Capacity (L)	41
Coolant Capacity (L)	29,6
Fuel Tank Capacity (L)	696
Maximum Exhaust Gas Temperature (°C)	496
Maximum Exhaust Gas Flow (m3/h)	2934
Maximum Back Pressure (kPa)	10
Cooling Air Flow (m3/min)	482
Fuel Consumption at 50 % (L/h)	33,1
Fuel Consumption at 75 % (L/h)	47,5
Fuel Consumption at 100 % (L/h)	63,1
Cylinder Liner Type	Wet Type-Replacable
Air Filter Type	Dry Type-Replacable
Radiator	Tropical type up to 50 °C

Alternator Specifications

Alternator Brand	Leroy Somer
Alternator Model	TAL046F
Frequency (Hz)	60
Nominal Power (kVA)	290
Nominal Voltage (V)	380
Phase	3
Regulated By	AVR
Voltage Regulation	± 0,8%
Short Circuit Current	100% In
Insulation	Class H
IP Class	IP 23
Power Factor	0.8
Efficiency (%)	93,2
THD	<2,5%
Connection Type	Star connection
Number of Wires	6
Poles	4 pole
Bearing Type	Single Bearing



Open Type Dimensions and Weight

Width (mm)	1300
Length (mm)	2700
Height (mm)	1730
Weight (Kg)	2400
Fuel Tank Capacity (L)	696

Starkgen reserves the right to introduce changes to models and features without prior notice

Canopy Type Dimensions and Weight

Width (mm)	1300
Length (mm)	4000
Height (mm)	2100
Weight (Kg)	2680
Fuel Tank Capacity (L)	696



STARKGEN JENERATÖR PAZARLAMA ve TİC. AŞ

Center Office

Hürriyet mah. Yakacık D100 Kuzey Yanyol
No49/1 34876 Kartal - İstanbul, Türkiye
T. +90 216 453 0404

Factory

Hanlı Sakarya Mah. Başak Sk. No 56/1
Arifiyе - Sakarya, Türkiye
T. +90 264 295 8300

