

## SGT-995PW6

Standby Power (kVA)	993
Standby Power (kW)	794,4
Prime Power (kVA)	899
Prime Power (kW)	719,2
Power Factor (cos phi)	0,8

Standby Current (A)	1510
Prime Current (A)	1368
Nominal Voltage (V)	380/220
Engine Speed (r.p.m)	1800
Phase	3

### Engine Specifications

Engine Brand	PERKINS
Engine Model	4008TAG1
Standby Power (Kw/hp)	899 /1205
Engine Speed (r.p.m)	1800
Total Displacement (L)	30,561
Cylinder Arrangement	8-L
Bore x Stroke (mm x mm)	160 x 190
Compretion Ratio	13,6:1
Governor Type	Electronic
Aspiration System	Turbocharged
Injection	Direct
Cooling System	Water Cooled
Electrical System (VDC)	24
Oil Capacity (L)	213
Coolant Capacity (L)	162
Fuel Tank Capacity (L)	External
Maximum Exhaust Gas Temperature (°C)	460
Maximum Exhaust Gas Flow (m3/h)	10374
Maximum Back Pressure (kPa)	10,7
Cooling Air Flow (m3/min)	1188
Fuel Consumption at 50 % (L/h)	99
Fuel Consumption at 75 % (L/h)	147
Fuel Consumption at 100 % (L/h)	199
Cylinder Liner Type	Wet Type-Replacable
Air Filter Type	Dry Type-Replacable
Radiator	Tropical type up to 50 °C

### Alternator Specifications

Alternator Brand	WEG
Alternator Model	355MI70AI
Frequency (Hz)	60
Nominal Power (kVA)	1150
Nominal Voltage (V)	380
Phase	3
Regulated By	AVR
Voltage Regulation	± 0,5%
Short Circuit Current	300% In
Insulation	Class H
IP Class	IP 23
Power Factor	0.8
Efficiency (%)	94,3
THD	<3%
Connection Type	Star connection
Number of Wires	12
Poles	4 pole
Bearing Type	Single Bearing



### Open Type Dimensions and Weight

Width (mm)	2438
Length (mm)	5800
Height (mm)	2250
Weight (Kg)	8000
Fuel Tank Capacity (L)	External

Starkgen reserves the right to introduce changes to models and features without prior notice

### Canopy Type Dimensions and Weight

Width (mm)	2440
Length (mm)	6000
Height (mm)	3050
Weight (Kg)	11300
Fuel Tank Capacity (L)	External



### STARKGEN JENERATÖR PAZARLAMA ve TİC. AŞ

Center Office  
Hürriyet mah. Yakacık D100 Kuzey Yanyol  
No49/1 34876 Kartal - İstanbul, Türkiye  
T. +90 216 453 0404

Factory  
Hanlı Sakarya Mah. Başak Sk. No 56/1  
Arifnye - Sakarya, Türkiye  
T. +90 264 295 8300

