

## SGT-1250SX

Standby Power (kVA)	1242,5
Standby Power (kW)	994
Prime Power (kVA)	1125
Prime Power (kW)	900
Power Factor (cos phi)	0,8

Standby Current (A)	1796
Prime Current (A)	1626
Nominal Voltage (V)	400/231
Engine Speed (r.p.m)	1500
Phase	3

### Engine Specifications

Engine Brand	SDEC
Engine Model	6WTAA35-G310
Standby Power (Kw/hp)	1120/1502
Engine Speed (r.p.m)	1500
Total Displacement (L)	35,1
Cylinder Arrangement	6 L
Bore x Stroke (mm x mm)	186 x 215
Compreion Ratio	15.0 : 1
Governor Type	ECU
Aspiration System	Turbocharged-Intercooler
Injection	Direct
Cooling System	Water Cooled
Electrical System (VDC)	24
Oil Capacity (L)	100
Coolant Capacity (L)	240
Fuel Tank Capacity (L)	1680
Maximum Exhaust Gas Temperature (°C)	650
Maximum Exhaust Gas Flow (m3/h)	10956
Maximum Back Pressure (kPa)	16
Cooling Air Flow (m3/min)	TBA
Fuel Consumption at 50 % (L/h)	125,7
Fuel Consumption at 75 % (L/h)	190
Fuel Consumption at 100 % (L/h)	259,2
Cylinder Liner Type	Dry Type
Air Filter Type	Heavy Duty
Radiator	Tropical type up to 50 °C

### Alternator Specifications

Alternator Brand	Lynx
Alternator Model	LX404F
Frequency (Hz)	50
Nominal Power (kVA)	1130
Nominal Voltage (V)	400
Phase	3
Regulated By	AVR
Voltage Regulation	± 1%
Short Circuit Current	100% In
Insulation	Class H
IP Class	IP 23
Power Factor	0.8
Efficiency (%)	95,7
THD	<1.5%
Connection Type	Star connection
Number of Wires	6
Poles	4 pole
Bearing Type	Single Bearing



### Open Type Dimensions and Weight

Width (mm)	2100
Length (mm)	4300
Height (mm)	2730
Weight (Kg)	8500
Fuel Tank Capacity (L)	1680

### Canopy Type Dimensions and Weight

Width (mm)	2100
Length (mm)	5900
Height (mm)	3467
Weight (Kg)	9720
Fuel Tank Capacity (L)	1680

Starkgen reserves the right to introduce changes to models and features without prior notice



### STARKGEN JENERATÖR PAZARLAMA ve TİC. AŞ

Center Office  
Hürriyet mah. Yakacık D100 Kuzey Yanyol  
No49/1 34876 Kartal - İstanbul, Türkiye  
T. +90 216 453 0404

Factory  
Hanlı Sakarya Mah. Başak Sk. No 56/1  
Arifıye - Sakarya, Türkiye  
T. +90 264 295 8300

