

SGT-46LW

Standby Power (kVA)	44,8
Standby Power (kW)	35,84
Prime Power (kVA)	40
Prime Power (kW)	32
Power Factor (cos phi)	0,8

Standby Current (A)	65
Prime Current (A)	58
Nominal Voltage (V)	400/231
Engine Speed (r.p.m)	1500
Phase	3

Engine Specifications

Engine Brand	LISTER PETER
Engine Model	SA432G2
Standby Power (Kw/hp)	39/52,3
Engine Speed (r.p.m)	1500
Total Displacement (L)	3,17
Cylinder Arrangement	4 - L
Bore x Stroke (mm x mm)	98 x 105
Compreion Ratio	18.5:1
Governor Type	Electronic
Aspiration System	Turbocharged
Injection	Direct
Cooling System	Water Cooled
Electrical System (VDC)	12
Oil Capacity (L)	8
Coolant Capacity (L)	13,25
Fuel Tank Capacity (L)	55
Maximum Exhaust Gas Temperature (°C)	385
Maximum Exhaust Gas Flow (m3/h)	402
Maximum Back Pressure (kPa)	10
Cooling Air Flow (m3/min)	39
Fuel Consumption at 50 % (L/h)	5,2
Fuel Consumption at 75 % (L/h)	7,33
Fuel Consumption at 100 % (L/h)	9,73
Cylinder Liner Type	Wet Type-Replacable
Air Filter Type	Dry Type-Replacable
Radiator	Tropical type up to 52 °C

Alternator Specifications

Alternator Brand	WEG
Alternator Model	201AIHS
Frequency (Hz)	50
Nominal Power (kVA)	41
Nominal Voltage (V)	400
Phase	3
Regulated By	AVR
Voltage Regulation	± 0,5%
Short Circuit Current	300% In
Insulation	Class H
IP Class	IP 23
Power Factor	0.8
Efficiency (%)	84,2
THD	<3%
Connection Type	Star connection
Number of Wires	12
Poles	4 pole
Bearing Type	Single Bearing



Open Type Dimensions and Weight

Width (mm)	1000
Length (mm)	1500
Height (mm)	1030
Weight (Kg)	860
Fuel Tank Capacity (L)	55

Canopy Type Dimensions and Weight

Width (mm)	1000
Length (mm)	2200
Height (mm)	1280
Weight (Kg)	1000
Fuel Tank Capacity (L)	55

Starkgen reserves the right to introduce changes to models and features without prior notice



STARKGEN JENERATÖR PAZARLAMA ve TİC. AŞ

Center Office
Hürriyet mah. Yakacık D100 Kuzey Yanyol
No49/1 34876 Kartal - İstanbul, Türkiye
T. +90 216 453 0404

Factory
Hanlı Sakarya Mah. Başak Sk. No 56/1
Arifıye - Sakarya, Türkiye
T. +90 264 295 8300

