

SGT-830SX

Standby Power (kVA)	825
Standby Power (kW)	660
Prime Power (kVA)	750
Prime Power (kW)	600
Power Factor (cos phi)	0,8

Standby Current (A)	1192
Prime Current (A)	1084
Nominal Voltage (V)	400/231
Engine Speed (r.p.m)	1500
Phase	3

Engine Specifications

Engine Brand	SDEC
Engine Model	6KTAA25-G32
Standby Power (Kw/hp)	754/1011
Engine Speed (r.p.m)	1500
Total Displacement (L)	25,2
Cylinder Arrangement	6 L
Bore x Stroke (mm x mm)	170 x 185
Compreion Ratio	14.5 : 1
Governor Type	ECU
Aspiration System	Turbocharged-Intercooler
Injection	Direct
Cooling System	Water Cooled
Electrical System (VDC)	24
Oil Capacity (L)	75
Coolant Capacity (L)	214
Fuel Tank Capacity (L)	1680
Maximum Exhaust Gas Temperature (°C)	600
Maximum Exhaust Gas Flow (m3/h)	7458
Maximum Back Pressure (kPa)	10
Cooling Air Flow (m3/min)	TBA
Fuel Consumption at 50 % (L/h)	82
Fuel Consumption at 75 % (L/h)	120
Fuel Consumption at 100 % (L/h)	161,5
Cylinder Liner Type	Dry Type
Air Filter Type	Heavy Duty
Radiator	Tropical type up to 50 °C

Alternator Specifications

Alternator Brand	Lynx
Alternator Model	LX354G
Frequency (Hz)	50
Nominal Power (kVA)	750
Nominal Voltage (V)	400
Phase	3
Regulated By	AVR
Voltage Regulation	± 1%
Short Circuit Current	100% In
Insulation	Class H
IP Class	IP 23
Power Factor	0.8
Efficiency (%)	95,2
THD	<1.5%
Connection Type	Star connection
Number of Wires	12
Poles	4 pole
Bearing Type	Single Bearing



Open Type Dimensions and Weight

Width (mm)	2100
Length (mm)	4300
Height (mm)	2730
Weight (Kg)	6440
Fuel Tank Capacity (L)	1680

Canopy Type Dimensions and Weight

Width (mm)	2100
Length (mm)	5900
Height (mm)	3467
Weight (Kg)	7660
Fuel Tank Capacity (L)	1680

Starkgen reserves the right to introduce changes to models and features without prior notice



STARKGEN JENERATÖR PAZARLAMA ve TİC. AŞ

Center Office
Hürriyet mah. Yakacık D100 Kuzey Yanyol
No49/1 34876 Kartal - İstanbul, Türkiye
T. +90 216 453 0404

Factory
Hanlı Sakarya Mah. Başak Sk. No 56/1
Arifıye - Sakarya, Türkiye
T. +90 264 295 8300

